

# **package-set**

## **Command Reference**

### **Table of contents**

1 Description.....	2
2 Usage.....	2
3 Examples.....	3

## 1. Description

*Set package data*

Define a [Package](#) object and its properties.

*static*: This command can be run outside of an object context.

## 2. Usage

```
ctl -m modelutil -c package-set [-arch <>] [-base <>]
[-buildtime <>] -depot <> [-description <>] [-filename <>]
[-filetype <>] [-installrank <>] [-installroot <>] -name <>
[-release <>] [-repourl <>] [-restart <>] -type <Package>
[-vendor <>] [-version <>]
```

### 2.1. Options

Option	Description	Type	Default
arch	<i>the package arch</i>	string	
base	<i>the package base</i>	string	
buildtime	<i>the package buildtime</i>	string	
<b>depot</b>	<i>project depot name</i>	string	<code> \${context.depot}</code>
description	<i>the package description</i>	string	
filename	<i>the package filename</i>	string	
filetype	<i>the package filetype</i>	string	
installrank	<i>the package installrank</i>	string	
installroot	<i>the package installroot</i>	string	
<b>name</b>	<i>logical package name</i>	string	
release	<i>the package release</i>	string	
repourl	<i>the package repourl</i>	string	
restart	<i>the package restart</i>	string	
<b>type</b>	<i>the package type</i>	string	Package

*package-set*

vendor	<i>the package vendor</i>	string	
version	<i>the package version</i>	string	

### 3. Examples

Define the data for a package not yet defined in the model.

```
ctl -p demo -m modelutil -c package-set -- -name apache-tomcat-5.5.26.zip  
-type zip\  
    -repourl  
http://strongbad:8080/jackrabbit/repository/workbench/pkgs/demo/zip/zips/apache-tomcat-  
    -base apache-tomcat-5.5.26 -filename  
apache-tomcat-5.5.26.zip -version 5.5.26 \  
    -installroot  
${env.CTIER_ROOT}/examples/service-package-deployment
```