

load-jobs

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2

1. Description

Load jobs into jobcenter via an XML file.

Uploads an XML file to Jobcenter containing Jobs in the jobs.xml format. The file is specified with the `-file` option. Connection options are required. When duplicate jobs already exist in Jobcenter, the action can be determined by specifying the `-dupeOption` option, whose values are iterated below:

static: This command can be run outside of an object context.

2. Usage

```
ctl -m ProjectBuilder -c load-jobs [-dupeoption <update>]
-file <> [-password <>] [-url <>] [-username <>]
```

2.1. Options

Option	Description	Type	Default
<code>dupeoption</code>	<p><i>Action to perform in case of a duplicate Job</i></p> <p>The behavior when encountering existing jobs with the same name can be changed by specifying one of the values below. The default is <code>update</code>.</p> <ul style="list-style-type: none"> <code>update</code> - Jobs with the same name will be updated to reflect the content in the file <code>create</code> - New Jobs will be created with the same name and the content in the file <code>skip</code> - Jobs will be skipped 	string	update
<code>file</code>	<i>Path to the jobs.xml file</i>	string	
<code>password</code>	<i>Jobcenter password</i>	string	<code>\${framework.server.password}</code>
<code>url</code>	<i>jobcenter server URL</i>	string	<code>\${framework.jobcenter.url}</code>

load-jobs

username	<i>Jobcenter Username</i>	string	<code>\${framework.server.username}</code>
----------	---------------------------	--------	--