

extract

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2

1. Description

Extract the package.

Checks to see if the rpm database exists. If not, creates it. Then uses rpm -Uvh to install the package with movable package prefix \${opts.installroot}. Uses sudo by default.

2. Usage

```
ctl -t rpm -o <objectname> -c extract [-base <>] -dbpath <>
-filename <> [-filtersfile <>] -installroot <> [-isrelocatable
<>] [-script <>] -url <> -usesudo <>
```

2.1. Options

Option	Description	Type	Default
base	<i>package base name</i>	string	\${entity.package-base}
dbpath	<i>rpm database path</i>	string	\${entity.attribute.rpmDbPath}
filename	<i>the filename</i>	string	\${entity.package-filename}
filtersfile	<i>filtersfile</i>	string	\${entity.package-filtersfile}
installroot	<i>the install root</i>	string	\${entity.package-install-root}
isrelocatable	<i>script to execute</i>	string	\${entity.attribute.rpmIsReloca}
script	<i>script to execute</i>	string	\${entity.attribute.package-ext}
url	<i>the repo url</i>	string	\${entity.package-repo-url}
usesudo	<i>whether to use sudo to run rpm</i>	string	\${entity.attribute.rpmUseSudo}