

startService

Command Reference

Table of contents

| | |
|--------------------|---|
| 1 Description..... | 2 |
| 2 Usage..... | 2 |

1. Description

start the service process

2. Usage

```
ctl -t Mule -o <objectname> -c startService [-configfile
<${entity.attribute.muleConfigFile}>] [-console] [-javahome
<>] [-mulebase <${entity.attribute.muleBase}>] [-mulehome
<${entity.attribute.muleHome}/${entity.attribute.mulePackageBase}>]
[-path <>]
```

2.1. Options

| Option | Description | Type | Default |
|------------|--|---------|---|
| configfile | <i>The location of the configuration file</i> | string | <code>\${entity.attribute.muleConfigFile}</code> |
| console | <i>Start Mule in console mode</i> | boolean | |
| javahome | <i>The Mule JAVA_HOME directory</i> | string | <code>\${entity.attribute.muleJavaHome}</code> |
| mulebase | <i>The Mule runtime directory</i> | string | <code>\${entity.attribute.muleBase}</code> |
| mulehome | <i>The Mule package installation directory</i> | string | <code>\${entity.attribute.muleHome}/\${entity.attribute.mulePackageBase}</code> |
| path | <i>The Mule PATH environment variable</i> | string | <code>\${entity.attribute.mulePath}</code> |