

Type Reference

- [AtgApacheServer](#): Apache web server
 - [AtgApachePath](#): The value of the PATH environment variable used to run the Apache server
 - [AtgApachePidFile](#): Location of the Apache server process identifier file
 - [AtgApacheServerConfigFile](#): Location of the Apache server configuration file
 - [AtgApacheSetting](#): Apache web server settings
 - [AtgApacheStartCommand](#): The command to use to start Apache via apachectl (usually "start" or "startssl")
 - [AtgApacheTimeout](#): Period to wait (in seconds) before timing out Apache server start/stop commands
 - [AtgApacheUser](#): Period to wait (in seconds) before timing out Apache server start/stop commands
- [AtgAppServer](#): An ATG application server
 - [AtgAppServername](#): The configuration name of the atg server
 - [AtgAppServerSetting](#): An ATG application server setting
 - [AtgAppTimezone](#): A appserver timezone
 - [AtgDirlist](#): The list of expected instance sub directories
 - [AtgRepositoryCache](#): The RMI component and method to manage flushing a local ATG repository cache
 - [AtgRmiHost](#): An RMI host
 - [AtgRmiPath](#): Path the the ControlTier RMI component dispatcher
 - [AtgRmiPort](#): An RMI listen port
 - [AtgSwitchingDatasource](#): An ATG switching datasource configuration item
- [AtgBuilder](#): General purpose ATG application builder
 - [BuilderImportPackagePattern](#): ATG Dynamo Live Config Directory Creation List setting
 - [BuilderScmUpdate](#): execute scm update instead of checkout if module appears to be checked out already. If false and module appears to be checked out then fail
- [AtgCatalogRdbSchema](#): An Atg Catalog schema
- [AtgCatalogSchemaPair](#): Association class between two schema objects
- [AtgCatalogUpdater](#): The product catalog data updater
- [AtgConfigBuilder](#): General purpose ATG config builder
- [AtgConfigJar](#): Jar file of ATG application server (local) configuration

- [AtgConfigUpdater](#): General purpose ATG application module updater
- [AtgDasInstallerJar](#): Jar file of ATG application server (local) configuration
- [AtgDasModuleBuilder](#): A builder sub-type customized to facilitate building and packaging ATG modules for the Dynamo application server
- [AtgDasServer](#): ATG Dynamo application server
 - [AtgDasArguments](#): The set of command line arguments to pass to dynamoStart for a given server
 - [AtgDasJavaHome](#): The JAVA_HOME to set for Dynamo server administration
 - [AtgDasPassword](#): Password to use for Dynamo server administration
 - [AtgDasPath](#): The PATH to set for Dynamo server administration
 - [AtgDasSetting](#): A DAS Setting
 - [AtgDasStartTimeout](#): Timeout period (in seconds) to wait for Dynamo startup to succeed
 - [AtgDasStopTimeout](#): Timeout period (in seconds) to wait for Dynamo shutdown to succeed
 - [AtgDasUser](#): User account to use for Dynamo server administration
- [AtgDataBuilder](#): General purpose ATG data builder
- [AtgDataUpdater](#): runs the corporate data update
- [AtgDynamo](#): The ATG Dynamo software installation (containing modules and ATG_HOME/DYNAMO_HOME)
 - [AtgAppServerCollectionSetting](#): an AtgAppServerCollection setting
 - [AtgDasRoot](#): The value of DAS_ROOT
 - [AtgDynamoInstallUnit](#): ATG install unit name
 - [AtgDynamoSetting](#): ATG Dynamo settings
 - [AtgEnvironment](#): An Atg environment
 - [AtgServerPattern](#): Type name or regex to dispatch commands
- [AtgEar](#): ATG Java enterprise application archive package
- [AtgJBossLocalConfig](#): A JBoss Environmental Configuration Zip Package
- [AtgJBossModuleBuilder](#): A builder sub-type customized to facilitate building and packaging ATG modules for the JBoss application server
 - [AtgJBossHome](#): Location of the JBoss installation
 - [AtgListenPort](#): JBoss listen port
- [AtgJBossServer](#): An ATG JBoss application server
 - [AtgCopyFromJBossDefaultInstance](#): configure new jboss instance from default if true
 - [AtgDataDir](#): Directory path to ATG-Data dir
 - [AtgDynamoModules](#): Directory path to ATG-Data dir
 - [AtgDynamoServerName](#):
 - [AtgJBBindAddr](#): JBoss Bind Address
 - [AtgJBInpPort](#): The name of an ATG JBoss Configuration

- [AtgJBjrmprmiObjectPort](#): JBoss JRMP RMI Object Port
- [AtgJBNamingRmiPort](#): JBoss Naming RMI Object Port
- [AtgJBossDirCreateList](#): ATG Dynamo Live Config Directory Creation List setting
- [AtgJBossDirRemoveList](#): ATG Dynamo Live Config Directory Removal List setting
- [AtgJBossDocumentRoot](#): JBoss Document Root
- [AtgJBossEngineLocalhostConfig](#): arbitrary tomcat engine/localhost configuration
- [AtgJBossExtractEar](#): JAVA_HOME for JBoss
- [AtgJBossJavaHome](#): JAVA_HOME for JBoss
- [AtgJBossJavaOpts](#): Set of Java options to include in the JBoss run.conf file
- [AtgJBossJvmRoute](#): time to wait for startup before timing out
- [AtgJBossLiveConfig](#): ATG Dynamo Live Config setting
- [AtgJBossPidfile](#): jboss transaction timeout
- [AtgJBossPortConfig](#): JBoss service bindings port configuration
- [AtgJBossSetting](#): A JBoss Setting
- [AtgJBossShutdownTimeout](#): time to wait for shutdown before timing out
- [AtgJBossStartupTimeout](#): time to wait for startup before timing out
- [AtgJBossTransactionTimeout](#): jboss transaction timeout
- [AtgJBPooledServerBindPort](#): JBoss Pooled Server Bind Port
- [AtgJBTCajpPort](#): Embedded Tomcat/JBoss AJP Port
- [AtgJBTChttpPort](#): JBoss HTTP Port
- [AtgJBUIL2ServerBindPort](#): JBoss UIL2 ServerBind Port
- [AtgJBWSPort](#): JBoss WebServices Port
- [AtgRmiPort](#): Dynamo server RMI port value used in "localconfig/atg/dynamo/Configuration.properties".
- [AtgJBossServerConfig](#): A JBoss Environmental Configuration Zip Package
- [AtgLicenseZip](#): A Zip archive of ATG license files
- [AtgMSSqlRdb](#): A SQL relational database service
 - [AtgMSSqlRdbInstanceName](#): Stores the value of an SQL name
 - [AtgMSSqlRdbSetting](#): an AtgMSSqlRdb setting
- [AtgMSSqlSchema](#): Represents an database schema
 - [AtgMSSqlSchemaSetting](#): an AtgMSSqlSchema setting
- [AtgMerchandising](#): ATG Merchandising for the ATG Development Platform
- [AtgModuleBuilder](#): A builder sub-type customized to facilitate building and packaging a single source code module
 - [AtgAntHome](#): The Ant installation directory
 - [AtgAntOpts](#): The Ant ANT_OPTS setting
 - [AtgBuilderSetting](#): An ATG module builder setting.
 - [AtgBuildFile](#): The location of the "top-level" build file relative to a CVS module's root directory

- [AtgCvs](#): Location of the CVS executable in the system
- [AtgCvsRoot](#): The value of the CVSROOT environment variable
- [AtgCvsRsh](#): The location of the program for CVS to use for remote connectivity
- [AtgDynamoHome](#): Location of the ATG Dynamo installation server home
- [AtgDynamoRoot](#): Location of the ATG Dynamo installation
- [AtgHome](#): The ATG installation directory
- [AtgJavaHome](#): Location of the Java installation
- [AtgModuleBranch](#): Branch name within the CVS repository (use TRUNK to indicate the main branch)
- [AtgModuleLabel](#): Label within the CVS repository (use HEAD to select the latest sources)
- [AtgModuleName](#): A module name within the CVS repository
- [AtgModulePackageType](#): Package subtype package is imported as
- [AtgPath](#): Value to use for the PATH environment variable when executing system binaries
- [AtgPreCompile](#): pre compile boolean flag
- [AtgTarget](#): Target used with a CVS module's top-level build file
- [AtgModuleJar](#): Jar file of an ATG module
- [AtgModuleUpdater](#): General purpose ATG application module updater
- [AtgOracleRdb](#): An Oracle relational database service
 - [AtgOracleRdbInstanceName](#): Stores the value of an Oracle TNS name
 - [AtgOracleRdbSetting](#): an AtgOracleRdb setting
- [AtgOracleSchema](#): Represents an database schema
 - [AtgOracleSchemaSetting](#): an AtgOracleSchema setting
- [AtgPatchJar](#): ATG patch Jar file
- [AtgPioneerCyclingProjectBuilder](#): Pioneer Cycling Project Builder demo
- [AtgPlatformInstaller](#): ATG (JBoss) Platform self-extracting installer package
- [AtgPlatformZip](#): Standard platform zip format package
- [AtgProjectBuilder](#): Builds and manages projects that use the ATG solution library
 - [AtgProjectBuilderDefaults](#): file containing project defaults properties
 - [AtgProjectBuilderSetting](#): A AtgProjectBuilder setting.
 - [AtgProjectBuilderTemplateDir](#): file containing project template files
- [AtgProjectUpdater](#): Updater type designed orchestrate the end-to-end build and deployment process
 - [NotificationList](#): List of email addresses used by the project updater for workflow success/failure notification
 - [Requestor](#): Email address of a project's owner
- [AtgRdb](#): A relational database service

- [AtgRdbConnection](#): Specifies the Database Connection
- [AtgRdbDriver](#): Specifies the Database Driver
- [AtgRdbEncryptedPassword](#): An encrypted rdb user's password
- [AtgRdbInstanceName](#): Stores the value of the database instance name
- [AtgRdbPassword](#): A schema user's password
- [AtgRdbPort](#): Specifies the Database Connection Port
- [AtgRdbSetting](#): an AtgRdb setting
- [AtgRdbType](#): Specifies the unique key value identifying which type database type is in use (e.g. "mssql" or "oracle", etc)
- [AtgRdbUserName](#): A user for a schema
- [AtgRdbData](#): A databases schema dump
 - [AtgRdbInstallRoot](#): Specifies the location where dump files are unpacked prior to being loaded into the target database.
 - [AtgRdbSetting](#): an AtgRdb setting
- [AtgRdbDataScripts](#): A databases schema dump
- [AtgRdbModuleScripts](#): A databases schema dump
- [AtgRdbOracleScripts](#): A databases schema dump
- [AtgRdbSchema](#): Represents a database schema
 - [AtgRdbDataSourceName](#): JNDI data source name for connecting to the schema
 - [AtgRdbMaxPoolSize](#): DataSource maximum connections
 - [AtgRdbMinPoolSize](#): DataSource minimum connections
 - [AtgRdbSchemaEncryptedPassword](#): An encrypted schema user's password
 - [AtgRdbSchemaName](#): A schema name
 - [AtgRdbSchemaPassword](#): A schema user's password
 - [AtgRdbSchemaSetting](#): an AtgRdbSchema setting
 - [AtgRdbSchemaTransactionIsolation](#): Schema Transaction Isolation value
 - [AtgRdbSchemaType](#): A schema name
 - [AtgRdbSchemaUserName](#): A user for a schema
- [AtgScriptsRdb](#): A SQL relational database service
- [AtgService](#): General purpose ATG service type
 - [AtgLocalConfig](#): Location of the local configuration directory for the service
 - [AtgServiceSetting](#): An ATG Service Setting
- [AtgSite](#): Controls the ATG Site
 - [AtgSiteSetting](#): General AtgSite settings
 - [AtgSiteSSHUser](#): The Setting which overrides the default ssh user when executing remote commands
- [AtgSolidRdb](#): Solid database service
- [AtgSolidRdbSchema](#): Represents a Solid database schema

- [AtgUpdater](#): General purpose ATG package updater
- [JcePolicyZip](#): Java Cryptology Extension Package
- [ServiceMediator](#): Mediates actions across multiple services