

AtgDataUpdater

runs the corporate data update

Table of contents

1 Overview.....	2
2 Design.....	2
3 Constraints.....	2
3.1 Allowed Child Dependencies.....	2
3.2 Allowed Parent Dependencies.....	2
4 Attributes.....	2
4.1 Defaults for Imported Attributes.....	3
5 Commands.....	3
5.1 Deploy.....	3
5.2 rdbSchemasImportDmp.....	3

1. Overview

AtgDataUpdater: runs the corporate data update

2. Design

Super Type

[AtgUpdater](#)

Role	Concrete. (Objects can be created.)
Instance Names	Unique
Notification	false
Template Directory	
Data View	Children, proximity: 1
Logger Name	AtgDataUpdater

3. Constraints

3.1. Allowed Child Dependencies

- [AtgBuilder](#)
- [AtgSite](#)
- DefaultDeploymentType1
- DefaultPackageName1
- DefaultPackageType1
- DispatchChangeDependencies1
- DispatchOptions1
- DispatchResourceType1

1: These types have a *Singleton* constraint. Only one instance may be added as a resource.

3.2. Allowed Parent Dependencies

- [AtgProjectUpdater](#)
- Node

4. Attributes

4.1. Defaults for Imported Attributes

Name	Default
defaultDeploymentType	AtgRdb
defaultPackageType	AtgRdbData
dispatchChangeDependencies	false
dispatchOptions	buildstamp
dispatchResourceType	AtgSite

5. Commands

Note:

Commandline options displayed in square brackets "[]" are optional. If an option expects arguments, then angle brackets are shown after the option "<>". Any default value is shown within the brackets.

5.1. Deploy

Runs the database dump import process

Usage

Deploy -buildstamp <>

5.1.1. Workflow

1. [rdbSchemasImportDmp](#)

Options

Option	Description
buildstamp	<i>build identifier</i>

5.2. rdbSchemasImportDmp

import the catalog data into the Site AtgOracleRdb

Usage

rdbSchemasImportDmp -buildstamp <> [-schematype
<.*RdbSchema>] [-session <update.session>]

Options

Option	Description
buildstamp	<i>buildstamp</i>
schematype	<i>schema type</i>
session	<i>workflow session data</i>