

repoPurge

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2

1. Description

Remove package objects from the repository.

Processes results of [repoFind](#) and removes each package from the repository - deleting the file from the webdav and object in the project model.

The `-packagename` and `-packagetype` arguments allow one to filter the `repoFind` result data, only purging objects matching those patterns.

2. Usage

```
ctl -t Builder -o <objectname> -c repoPurge [-buildertype <>]
[-buildstamp <>] [-ignoreparents <>false>] [-packagename <.*>]
[-packagetype <>] [-session <repoFind.session>]
```

2.1. Options

Option	Description	Type	Default
<code>buildertype</code>	<i>builder type</i>	string	<code>\${context.type}</code>
<code>buildstamp</code>	<i>build identifier (regex allowed)</i>	string	<code>\${entity.attribute.packagePurge}</code>
<code>ignoreparents</code>	<i>delete package even if it is associated with a parent resource</i>	string	false / <code>\${entity.attribute.packagePurge}</code>
<code>packagename</code>	<i>package name</i>	string	<code>.*</code>
<code>packagetype</code>	<i>type (or subtype) of package to find</i>	string	<code>\${entity.attribute.packageType}</code>
<code>session</code>	<i>session results are stored</i>	string	<code>repoFind.session</code>