

package-set

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2
3 Examples.....	3

1. Description

Set package data

Define a [Package](#) object and its properties.

static: This command can be run outside of an object context.

2. Usage

```
ctl -m modelutil -c package-set [-arch <>] [-base <>]
[-buildtime <>] [-depot <>] [-description <>] [-filename <>]
[-filetype <>] [-installrank <>] [-installroot <>] -name <>
[-release <>] [-repourl <>] [-restart <>] -type <Package>
[-vendor <>] [-version <>]
```

2.1. Options

Option	Description	Type	Default
arch	<i>the package arch</i>	string	
base	<i>the package base</i>	string	
buildtime	<i>the package buildtime</i>	string	
depot	<i>project depot name</i>	string	<code>\${context.depot}</code>
description	<i>the package description</i>	string	
filename	<i>the package filename</i>	string	
filetype	<i>the package filetype</i>	string	
installrank	<i>the package installrank</i>	string	
installroot	<i>the package installroot</i>	string	
name	<i>logical package name</i>	string	
release	<i>the package release</i>	string	
repourl	<i>the package repourl</i>	string	
restart	<i>the package restart</i>	string	
type	<i>the package type</i>	string	Package

package-set

vendor	<i>the package vendor</i>	string	
version	<i>the package version</i>	string	

3. Examples

Define the data for a package not yet defined in the model.

```
ctl -p demo -m modelutil -c package-set -- -name apache-tomcat-5.5.26.zip
-type zip\
    -repourl
http://strongbad:8080/jackrabbit/repository/workbench/pkgs/demo/zip/zips/apache-tomcat-
-base apache-tomcat-5.5.26 -filename
apache-tomcat-5.5.26.zip -version 5.5.26 \
    -installroot
${env.CTIER_ROOT}/examples/service-package-deployment
```