

email

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2

1. Description

Sends an email.

static: This command can be run outside of an object context.

2. Usage

```
ctl -m netutil -c email [-cc <>] [-failonerror <true>] [-files
<>] [-from <>] -host <> [-message <>] [-messagefile <>]
[-mimetype <text/html>] [-password <>] -port <> [-replyto <>]
[-ssl <false>] -subject <> -to <> [-user <>]
```

2.1. Options

Option	Description	Type	Default
cc	<i>Recipients to carbon copy</i> Comma-separated list of recipients.	string	
failonerror	<i>Fail if email cannot be delivered.</i> Causes command to exit with an error. Results in additional verbose messages, too.	string	true / \${framework.email.failonerror}
files	<i>Files to attach to message</i> Files to send as attachments to the email. Separate multiple file names using a comma or space.	string	
from	<i>The sender email address</i>	string	\${framework.email.from}
host	<i>The mail server.</i>	string	\${framework.email.mailhost}
message	<i>The message content</i>	string	
messagefile	<i>The message file</i>	string	

email

mimetype	<i>The content type of the message</i> The default is text/html but could also be text/plain.	string	text/html
password	<i>Password for SMTP auth</i>	string	\${framework.email.password}
port	<i>The port number to connect to.</i>	string	\${framework.email.mailport}
replyto	<i>The message replyto address</i>	string	\${framework.email.replyto}
ssl	<i>Connect using ssl.</i>	string	false / \${framework.email.ssl}
subject	<i>Email subject line</i>	string	
to	<i>The message recipient</i> Comma-separated list of recipients.	string	
user	<i>User name for SMTP auth</i>	string	\${framework.email.user}