

register

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2

1. Description

Register the package to the repository.

static: This command can be run outside of an object context.

2. Usage

```
ctl -m Package -c register [-arch <>] [-base <>] [-buildtime <>] [-depot <>] [-description <>] [-filename <>] [-filetype <>] [-installrank <>] [-installroot <>] [-name <>] [-release <>] [-releasetag <>] [-restart] [-type <>] [-url <>] [-vendor <>] [-version <>] [-xml <>]
```

2.1. Options

Option	Description	Type	Default
arch	<i>host architecture</i>	string	
base	<i>the package base name</i>	string	
buildtime	<i>time package was built</i>	string	
depot	<i>project depot name</i>	string	
description	<i>description of the object</i>	string	
filename	<i>the file name</i>	string	
filetype	<i>the package file type</i>	string	
installrank	<i>install rank</i>	string	
installroot	<i>the installation root</i>	string	
name	<i>the object name</i>	string	
release	<i>the package release</i>	string	
releasetag	<i>release tag</i>	string	
restart	<i>requires restart</i>	boolean	
type	<i>the object type</i>	string	

register

url	<i>the repo url</i>	string	
vendor	<i>the package producer</i>	string	
version	<i>the package version</i>	string	
xml	<i>xml file containing object data</i>	string	