

BitTorrentTracker

BitTorrent tracker server

Table of contents

1 Overview.....	2
2 Design.....	2
3 Constraints.....	2
4 Attributes.....	2
5 Commands.....	2
6 Related Types.....	3

1. Overview

BitTorrentTracker: *BitTorrent tracker server*

2. Design

Super Type Service

Role	Concrete. (Objects can be created.)
Instance Names	Unique
Notification	false
Template Directory	
Data View	Children, proximity: 1
Logger Name	BitTorrentTracker

3. Constraints

3.1. Allowed Child Dependencies

- [BitTorrentTrackerPort](#) 1
- BitTorrentTrackerUrl1

1: These types have a *Singleton* constraint. Only one instance may be added as a resource.

3.2. Allowed Parent Dependencies

- Node
- Site

4. Attributes

4.1. Defaults for Imported Attributes

Name	Default
trackerPort	6881

5. Commands

View the available commands in the [User Reference](#).

6. Related Types

The following types are defined for use with BitTorrentTracker.

6.1. BitTorrentTrackerPort

6.1.1. Overview

BitTorrentTrackerPort: *BitTorrent tracker port*

6.1.2. Design

Super Type

[BitTorrentTrackerSetting](#)

Role	Concrete. (Objects can be created.)
Instance Names	Unique

6.1.3. Attributes

6.1.3.1. Exported Attributes

Name	Property
trackerPort	settingValue

6.2. BitTorrentTrackerSetting

6.2.1. Overview

BitTorrentTrackerSetting: *A BitTorrent tracker server setting*

6.2.2. Design

Super Type

Setting

Role	Abstract. (Objects cannot be created.)
Instance Names	Unique

6.2.3. Constraints

6.2.3.1. Allowed Parent Dependencies

- [BitTorrentTracker](#)