

configureClient

Command Reference

Table of contents

1 Description.....	2
2 Usage.....	2

1. Description

configure a new controltier client

Concrete implementation and is meant to be called by the Deploy workflow command.

2. Usage

```
ctl -t ClientInstaller -o <objectname> -c configureClient
[-cygwinClient <>] [-frameworkServerHostname <>]
[-frameworkServerPassword <>] [-frameworkServerPort <>]
[-frameworkServerUsername <>] [-reportcenterPort <>]
-targetCTierRoot <> -targetHostname <> [-targetUser <>]
[-trustClient <false>]
```

2.1. Options

Option	Description	Type	Default
cygwinClient	<i>configure cygwin client</i>	string	\${entity.attribute.cygwinClient}
frameworkServerHos	<i>framework server hostname</i> defaults to the framework server hostname	string	
frameworkServerPas	<i>framework password</i> defaults to the framework server password	string	\${framework.server.password}
frameworkServerPor	<i>framework server port</i> defaults to the framework server port	string	
frameworkServerUse	<i>framework username</i> defaults to the framework server username	string	\${framework.server.username}
reportcenterPort	<i>reportcenter port</i> defaults to the reportcenter port	string	
targetCTierRoot	<i>client target</i>	string	\${entity.attribute.targetCTier}

configureClient

	<i>CTIER_ROOT</i>		
targetHostname	<i>client target hostname</i>	string	
targetUser	<i>client target user</i>	string	<code>\${entity.attribute.targetUser}</code>
trustClient	<i>trust remote clients when remotely executing</i>	string	false / <code>\${entity.attribute.trustClient}</code>