

SystemService

Unix/Linux system service module

Table of contents

1 Overview.....	2
2 Design.....	2
3 Constraints.....	2
4 Attributes.....	2
5 Commands.....	3
6 Related Types.....	3

1. Overview

SystemService: *Unix/Linux system service module*

SystemService uses the `/etc/init.d/` scripts to manage services, optionally via `sudo`.

2. Design

Super Type Service

Role	Concrete. (Objects can be created.)
Instance Names	Unique
Notification	false
Template Directory	
Data View	Children, proximity: 1
Logger Name	SystemService

3. Constraints

3.1. Allowed Child Dependencies

- Package
- Service
- [SystemServiceScript](#) 1
- [SystemServiceUseSudo](#) 1

1: These types have a *Singleton* constraint. Only one instance may be added as a resource.

3.2. Allowed Parent Dependencies

- Node
- Site

4. Attributes

4.1. Defaults for Imported Attributes

Name	Default
------	---------

systemServiceUseSudo	true
----------------------	------

5. Commands

View the available commands in the [User Reference](#).

6. Related Types

The following types are defined for use with SystemService.

6.1. SystemServiceScript

6.1.1. Overview

SystemServiceScript: *The name of the system service script in /etc/init.d*

This must be set in order to use this module directly. You can also set an attribute-default for systemServiceScript in your subtype.

6.1.2. Design

Super Type

[SystemServiceSetting](#)

Role	Concrete. (Objects can be created.)
Instance Names	Unique

6.1.3. Attributes

6.1.3.1. Exported Attributes

Name	Property
systemServiceScript	settingValue

6.2. SystemServiceSetting

6.2.1. Overview

SystemServiceSetting: *An System Service setting.*

6.2.2. Design**Super Type
Setting**

Role	Abstract. (Objects cannot be created.)
Instance Names	Unique

6.2.3. Constraints**6.2.3.1. Allowed Parent Dependencies**

- [SystemService](#)

6.3. SystemServiceUseSudo**6.3.1. Overview**

SystemServiceUseSudo: *Indicate whether sudo should be used to run the commands necessary to manage system services*

Defaults to true.

6.3.2. Design**Super Type
[SystemServiceSetting](#)**

Role	Concrete. (Objects can be created.)
Instance Names	Unique

6.3.3. Attributes**6.3.3.1. Exported Attributes**

Name	Property
systemServiceUseSudo	settingValue